


SPEZIFIKATIONEN

GÄNGE	24-SPEED	VORDERE NABE	SHIMANO DH-3D37 HUB DYNAMO, 6V, 3W, 32 HOLES
RAHMEN	TOURING CONCEPT, ALLOY 6061, WIEGE 700C	HINTERE NABE	SHIMANO FH-RM35, 32 HOLES, QR
RAHMENGRÖSSE	44CM,48CM,52CM	KASSETTE	SHIMANO CS-HG31, 11-34 TEETH, 8-SPEED
GABEL	SUNTOUR SF16-NEX DS, TAPERED, COIL SPRING, 63MM	KETTE	SHIMANO CN-HG71
VORBAU	BIXS AS-4002, ANGLE ADJUSTABLE, 31.8MM CLAMP	REIFEN	SCHWALBE DELTA CRUISER PLUS, PUNCTURE GUARD, 700X47C
STEUERSATZ	FSA NO.57E, 1-1/8" UPPER AND 1.5" LOWER BEARING WITH 12.3MM TOP COVER	GEPÄCKTRÄGER	RACKTIME BIXS CUSTOM WITH INTEGRATED REAR LIGHT
LENKER	BIXS HB-TR2 TREKKING BAR, 640MM, 25° ANGLE, 31.8MM	SCHUTZBLECHE	YUNG FANG EX-CP55-AB, 55MM WIDE, 700C
SCHALTWERK	SHIMANO ACERA RD-M360 SGS TOP NORMAL, 8-SPEED	DYNAMO	SHIMANO DH-3D37 HUB DYNAMO, 6V, 32W, 32 HOLES
UMWERFER	SHIMANO TOURNEY FD-TY710-TS3, TOP SWING, 34,9MM CLAMP	SCHEINWERFER	TRELOCK LS-383 LED, 50 LUX, STANDLIGHT AUTOMATIC
SCHALTHEBEL	SHIMANO SL-M315, WITH OPTICAL GEAR DISPLAY	RÜCKLICHT	INTEGRATED IN CARRIER, STANDLIGHT AUTOMATIC
BREMSHEBEL	SHIMANO BL-MT201	GEWICHT	16.9 KG
BREMSEN	SHIMANO BR-MT200, HYDRAULIC DISC BRAKE WITH RESIN PADS, F:160MM, R:160MM ROTORS	ARTIKELNUMMER	101-506-1096
KURBELGARNITUR	SHIMANO FC-TY501, 48-38-28T		
INNENLAGER	SHIMANO BB-UN300-K, 68MM X 122.5MM		
PEDALE	WELLGO LU-C097		
SATTELSTÜTZE	BIXS SP-3D2, 350MM, 31.6MM		
SATTEL	BIXS VL-3534		
FELGEN	ALEXRIMS MD-19, 32 HOLES, INNER WIDTH 19MM, 700C		

GEOMETRIE

SIZE	A	B	C	D	E	F	G	H	I	J	K
44cm	440	555	180	460	73°	70°	1068	90	--	--	--
48cm	480	570	180	460	73°	70°	1083	90	--	--	--
52cm	520	590	180	460	73°	70°	1103	100	--	--	--



A	Rahmengrösse
B	Oberrohr horizontal mm
C	Steuerrohr mm
D	Kettenstreben mm
E	Sitzwinkel Grad
F	Steuerrohrwinkel Grad
G	Radstand mm
H	Vorbau mm
I	Stack mm
J	Reach mm
K	Tretlagerhöhe mm

GRÖSSENRECHNER

KÖRPERGRÖSSE / TAILLE	147–163 cm	159–178 cm	174–188 cm
FAHRRADGRÖSSE	44cm	48cm	52cm

NOTIZEN / FIRKENSTEMPEL