


SPEZIFIKATIONEN

GÄNGE	12-SPEED
RAHMEN	SPORT GEOMETRY ALLOY 6061 HYDROF. T.B., DROPOUT 148X12MM BOOST, HARDTAIL 29"
RAHMENGRÖSSE	15",17",19",21"
GABEL	ROCK SHOX REBA RL 29", SOLO AIR SPRING, TAPERED, 15X110MM AXLE, 100MM TRAVEL, REBOUND, LOCKOUT
VORBAU	BIXS AS-M03, 0° ANGLE, 31.8MM CLAMP
STEUERSATZ	FSA NO.57, 1-1/8" UPPER AND 1.5" LOWER BEARING WITH 5.3MM TOP COVER
LENKER	BIXS HB-RB12W RIZER BAR, 760MM, 9° ANGLE, 25MM RISE, 31.8MM
SCHALTWERK	SHIMANO XT RD-M8100 SGS SHADOW PLUS DESIGN, 12-SPEED
SCHALTHEBEL	SHIMANO XT SL-M8100, DIRECT ATTACH TO BRAKE LEVER, ISPEC EV
BREMSHEBEL	SHIMANO XT BL-M8100, ISPEC EV
BREMSEN	SHIMANO XT BR-M8100, HYDRAULIC DISC BRAKE, RESIN PADS, F:180MM, R:180MM ROTORS
KURBELGARNITUR	SHIMANO XT FC-M8100-1, HOLLOWTECH II, 32 TEETH
INNENLAGER	SHIMANO BB-MT800
PEDALE	WELLGO WPD-823, WITH CLEAT

SATTELSTÜTZE	BIXS SP-719, 15" & 17": 350MM, OTHERS: 400MM, 31.6MM
SATTEL	ERGON SR10 SPORT
FELGEN	ALEXRIMS EXR-27, 32 HOLES, INNER WIDTH 27MM, 29"
VORDERE NABE	SHIMANO XT HB-M8110-B, 32 HOLES, 15X110MM THRU AXLE
HINTERE NABE	SHIMANO XT FH-M8110-B, 32 HOLES, 12X148MM BOOST THRU AXLE
KASSETTE	SHIMANO CS-M7100, 10-51 THEETH, 12-SPEED
KETTE	SHIMANO CN-M8100 12-SPEED
REIFEN	SCHWALBE ROCKET RON PERFORMANCE, ADDIX, 29X2.25"
GEWICHT	11.4 KG
ARTIKELNUMMER	101-506-1073

GEOMETRIE

SIZE	A	B	C	D	E	F	G	H	I	J	K
15"	380	570	105	450	73°	69°	1089	35	621	380	300
17"	430	590	110	450	73°	69°	1110	45	626	399	300
19"	480	610	120	450	73°	69°	1130	55	635	415	300
21"	530	630	130	450	73°	69°	1156	65	645	432	300



A	Rahmengrösse
B	Oberrohr horizontal mm
C	Steuerrohr mm
D	Kettenstreben mm
E	Sitzwinkel Grad
F	Steuerrohrwinkel Grad
G	Radstand mm
H	Vorbau mm
I	Stack mm
J	Reach mm
K	Tretlagerhöhe mm

GRÖSSENRECHNER

KÖRPERGRÖSSE / TAILLE 149–163 cm 159–178 cm 174–188 cm 185–200 cm

FAHRRADGRÖSSE 15" 17" 19" 21"

NOTIZEN / FIRKENSTEMPEL